

PRODUCT INFORMATION

Purgex™ 458 Plus Commercial Purging Compound is a ready-to-use blend consisting of active ingredients with a polyethylene carrier. Purgex™ products have mechanical activity for efficient cleaning, foaming action for enhanced mixing and a lubricant for easy removal. Purgex™ thoroughly and safely cleans injection molding machines and hot runner systems.

Physical Description:

- Blend, polyethylene, viscosity modifier, and an active component
- Non-toxic, non-abrasive, and safe
- Ready to use and easy to remove

Process:	<input checked="" type="checkbox"/> Injection Molding	<input type="checkbox"/> Injection Blow Molding	<input checked="" type="checkbox"/> Extrusion-Blow Molding	<input checked="" type="checkbox"/> Extrusion-Profile
	<input checked="" type="checkbox"/> Extrusion-Compounding	<input checked="" type="checkbox"/> Extrusion-Sheet	<input type="checkbox"/> Blown Film	
Works Best on These Resins:	<input checked="" type="checkbox"/> PP-Copolymer	<input checked="" type="checkbox"/> ABS	<input checked="" type="checkbox"/> TPOs	<input checked="" type="checkbox"/> TPEs
	<input checked="" type="checkbox"/> PC/ABS	<input checked="" type="checkbox"/> POM		
Also Useful for:	<input checked="" type="checkbox"/> PBT	<input checked="" type="checkbox"/> Nylon	<input checked="" type="checkbox"/> Startup	<input checked="" type="checkbox"/> Shutdown
	<input checked="" type="checkbox"/> Many other resins processed in this temperature range.			
Amount Needed:	1 to 1.5 times barrel capacity, depending on condition of machine/tool and colorant/ additive loading.			
Temperature Range:	380°F to 550°F (193°C to 288°C)			
Recommended for:	<input checked="" type="checkbox"/> Hot Runners	<input checked="" type="checkbox"/> Mixing Nozzles	<input checked="" type="checkbox"/> Check Valves	<input type="checkbox"/> Accumulators
	<input checked="" type="checkbox"/> Cold Runners	<input checked="" type="checkbox"/> Extrusion Dies	<input checked="" type="checkbox"/> Melt Pumps	

Features & Benefits:

- ✓ Designed for tough applications plus efficient cleaning of hot runner systems, Purgex™ 458 Plus has proven to be particularly effective in removing resins with high pigment loading and/or high additive content. As well, Purgex™ 458 Plus is versatile and is effective on a wide variety of resins.
- ✓ Engineered for rapid turnaround on color and material changes. Efficiently removes residual contamination.
- ✓ Effectively cleans the barrel, screw, check ring, as well as hot runner systems and is safely processed through hot runner gates as small as .030-inch (0.75mm).
- ✓ Thorough cleaning of melt pumps and is safely processed through dies as small as .030-inch (0.75mm).
- ✓ Active components in Purgex™ 458 Plus neutralize acid gases generated by PVC.
- ✓ With regular use, Purgex™ forms a temporary barrier which protects steel surfaces from oxidation, extending the cleaning process.